

storing the static information into the editable field;  
receiving an indication that a roaming device is within the communications range;  
creating a record, the record being arranged to include information associated  
with the roaming device;  
5 adding the static information into the record; and  
storing the record in the database.

18. The method of claim 17 wherein the static information is received from a source  
external to the transceiver device.

19. The method of claim 17 wherein the record is created after the indication that the  
roaming device is within the communications range is received.

20. The method of claim 17 wherein adding the static information into the record  
15 includes reading the static information from the editable field.

21. The method of claim 17 wherein the static information is information associated  
with a location of the transceiver device.

22. The method of claim 17 wherein the transceiver device is an access point.

23. The method of claim 17 further including:  
obtaining the information associated with the roaming device when the indication  
that the roaming device is within the communications range is received.

24. A method of configuring an access point comprising:  
positioning the access point at a desired location;  
determining an address of the desired location; and  
storing the address in a memory field, the memory field being associated with the  
30 access point.

25. The method of claim 24 wherein the address includes at least one of a longitude, a latitude, and an altitude of the desired location.

5 26. The method of claim 24 wherein the address is determined using a global positioning system receiver.

27. The method of claim 24 wherein the memory field is an editable field, and storing the address in the memory field includes:

10 inputting the address into the access point.

28. The method of claim 27 wherein inputting the address into the transceiver device includes providing the address to the memory field.